



### Reduce downtime and leg damage: Add a proximity sensor

Stabilization legs can be damaged during travel if they're not fully retracted. Upgrade your stabilization system with Power-Packer's hydraulic stabilization legs, available with proximity sensor capabilities.



Proximity Equipped Leg – 3.5 in. (89 mm) bore – Load capacity 24,000 lbs. or 106.8 kN										
Part No.	Stroke		Mounting Height		Shoe Diameter		Shoe Type	Weight		Valve Type
	in.	mm	in.	mm	in.	mm		lbs.	kg	
9010001520	15	381	24.75	629	10	254	Fixed	85	38.56	PO Check
9010001521	20	508	29.65	753	12	305	Swivel	100	45.36	PO Check
9010001522	20	508	25.5	648	12	305	Swivel	110	49.9	PO Check
9010001523	24	610	14.4	366	Knuckle		Ball End	105	47.63	DCBV
9010001524	24	610	34.5	876	12	305	Swivel	115	52.16	PO Check
9010001525	25.5	648	12.75	324	16	406	Swivel	100	45.36	PO Check
9010001526	29.5	749	13.5	343	12	305	Swivel	135	61.23	PO Check
9010001527	34.5	876	12.75	324	16	406	Swivel	145	65.77	PO Check

  

Proximity Equipped Leg – 4 in. (102 mm) bore – Load capacity 31,000 lbs. or 137.9 kN										
9010001497	20.5	521	29.9	760	12	305	Swivel	160	72.57	DCBV
9010001528	14.8	375	24.8	629	10	254	Fixed	105	47.63	DCBV
9010001529	16.5	419	28	711	12	305	Swivel	110	49.9	DCBV
9010001531	24.5	622	22	558	12	305	Swivel	130	58.97	DCBV
9010001532	24.5	622	33.9	860	12	305	Swivel	135	61.23	DCBV
9010001533	25.5	648	13	330	16	406	Swivel	150	68.04	DCBV
9010001534	36	914	30	761	12	305	Swivel	170	77.11	DCBV

Proximity Sensor Kit	
Part No.	Part Name
1010003864	Kit, Proximity Switch Normally Open (NO) with Cable
1010003865	Kit, Proximity Switch Normally Closed (NC) with Cable

